

**ELATION® TVL PANEL DW™**  
**DMX Channel Values / Functions (7 Total DMX Channels)**

Supports Software Versions ≥: v1.1

Features subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
2	3	4	5	6	7		
	1		1	1	1		<b>WARM WHITE LEDS</b>
						0-255	Warm White (0=Black - 255=100%)
	2		2	2	2		<b>COOL WHITE LEDS</b>
						0-255	Cool White (0=Black - 255=100%)
1		1			3		<b>COLOR TEMPERATURE - LINEAR VARIABLE WHITE</b>
						0	OFF
						1-255	3,200K - 5,800K (0=3,200K - 255=5,800K)
				3	4		<b>SHUTTER / STROBE</b>
						0-31	LEDs OFF
						32-63	LEDs ON
						64-95	Strobe Effect SLOW to FAST
						96-127	LEDs ON
						128-159	Pulse Effect SLOW to FAST
						160-191	LEDs ON
						192-223	Random Strobe SLOW to FAST
						224-255	LED ON
2	3	2	3	4	5		<b>MASTER DIMMER INTENSITY</b>
						0-255	Intensity 0 to 100%
		3	4	5	6		<b>MASTER DIMMER INTENSITY FINE</b>
						0-255	Dimmer Intensity FINE Adjustment
		4	5	6	7		<b>DIMMER CURVES</b>
						0-20	STANDARD
						21-40	STAGE
						41-60	TV
						61-80	ARCHITECTURAL
						81-100	THRATRE
						101-255	DEFAULT to UNIT CURVE SETTING

**ELATION** | **TVL PANEL DW™** | dmx traits

**Elation Professional USA** | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

**Elation Professional B.V.** | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)