



## DTW BLINDER 350 IP™

SKU# DTW350

The IP65 rated DTW Blinder 350 IP™ is a 350W LED blinder luminaire featuring (2) high powered 175W 2-in-1 Warm White / Amber COB LEDs, pixel control, each pixel producing a 15° narrow beam angle with included fresnel lens filters or a 65° wide beam with lens removed, a unique "Dim-to-Warm" function that allows dimming from 1,800K to 3,200K, manual adjustable pan focus, electronic strobe and variable dimming curve effects, flicker free operation for TV and Film, RDM (Remote Device Management), IP rated 5pin DMX and powerCON TRUE1 in/out connections, LCD menu display with 4 touch button control panel, integrated yoke and side mounting brackets, and a multi-voltage universal auto switching power supply (100-250v).



### FEATURES

**IP65 Rated 350W COB LED Blinder Luminaire**

**(2) 175W 2-in-1 Warm White / Amber COB LEDs**

**>6,000 Lumens | >92 CRI**

**Pixel Control**

**15° Narrow Beam with included Fresnel Lens**

**65° Wide Beam with Fresnel Lens Removed**

**Dim-to-Warm Channel Control (1,800 - 3,200K)**

**RDM (Remote Device Management)**

**Flicker Free Operation for Broadcast TV and FILM**

**Rugged Die-Cast Aluminum Exterior**

**Multiple Unit Power Linking**



**PRODUCT SPECIFICATIONS**

**SOURCE**

(2) 175W 2-in-1 Warm White / Amber COB LEDs  
50,000 Hour Average LED Life\*

\*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, and Usage Patterns (On-Off Cycling, Control and Dimming).

**PHOTOMETRIC DATA**

4,216 LUX 391.7 FC @9.8' (3m) (15° Fresnel Lens Full ON)  
593 LUX 55.1 FC @9.8' (3m) (65° Full ON)

**EFFECTS**

Pixel Control  
15° Narrow Beam Angle with Included Fresnel Lens  
65° Wide Beam Angle with Fresnel Lens Removed  
Unique Dim-to-Warm Channel Control (1.800K - 3.200K)  
Electronic Strobe and Variable Dimming Curves

**COLOR**

Warm White / Amber

**CONTROL / CONNECTIONS**

(9) DMX Channel Modes (9 Total Channels)  
RDM (Remote Device Management)  
(4) Button TouchControl Panel  
IP Rated 5pin DMX In/Out  
powerCON TRUE 1 In/Out

**SIZE / WEIGHT**

Length: 15.74" (400mm)  
Width: 9.46" (240.5mm)  
Vertical Height: 9.64" (245mm)  
Weight: 18.0 lbs. (8.2 kg)

**ELECTRICAL / THERMAL**

AC 110-240V - 50/60Hz  
310W Max Power Consumption  
Multiple Unit Power Linking  
5°F to 113°F (-15°C to 45°C)

**INCLUDED ITEMS**

(2) 15° Narrow Beam Fresnel Lens  
powerCON TRUE1 Power Cable

**APPROVALS / RATINGS**




IP65




**PHOTOMETRIC DATA**


\*with included Fresnel lens attached



\*NO Fresnel lens attached



**DIMENSIONAL DIAGRAMS**



**OPTIONAL ACCESSORIES**

| ORDER CODE          | ITEM                                       |
|---------------------|--|
| <b>NARROW CLAMP</b> | PRO 2" Wrap Around Clamp                   |
| <b>805000053</b>    | Omega Bracket (107mm)                      |
| <b>NEU088</b>       | 3 ft. (1m) PowerCON TRUE1 Power Link Cable |
|                     | Additional cable lengths available         |



Specifications are subject to change without notice ©Elation Professional 08/07/17

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040  
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands  
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu