

ELATION® TVL CYC RGBW™
DMX Channel Values / Functions (14 DMX Channels)

Supports Software Versions: ≥ A: v1.2 | ≥ B: v1.1

Features subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
4	6	7	8	10	14		
1	1	1	1	1	1		RED
						0-255	Red (0-Black , 255-100% Red)
					2		RED FINE
						0-255	Red FINE Adjustment
2	2	2	2	2	3		GREEN
						0-255	Green (0-Black , 255-100% Green)
					4		GREEN FINE
						0-255	Green FINE Adjustment
3	3	3	3	3	5		BLUE
						0-255	Blue (0-Black , 255-100% Blue)
					6		BLUE FINE
						0-255	Blue FINE Adjustment
4	4	4	4	4	7		WHITE
						0-255	White (0-Black , 255-100% White)
					8		WHITE FINE
						0-255	White FINE Adjustment
				5	9		COLOR MACROS
						0-4	Preset Color 1
						5-8	Preset Color 2
						9-12	Preset Color 3
						13-16	Preset Color 4
						17-20	Preset Color 5
						21-24	Preset Color 6
						25-28	Preset Color 7
						29-32	Preset Color 8
						33-36	Preset Color 9
						37-40	Preset Color 10
						41-44	Preset Color 11
						45-48	Preset Color 12
						49-52	Preset Color 13
						53-56	Preset Color 14
						57-60	Preset Color 15
						61-64	Preset Color 16
						65-68	Preset Color 17
						69-72	Preset Color 18
						73-76	Preset Color 19
						77-80	Preset Color 20
						81-84	Preset Color 21
						85-88	Preset Color 22
						89-92	Preset Color 23
						93-96	Preset Color 24
						97-100	Preset Color 25
						101-104	Preset Color 26
						105-108	Preset Color 27
						109-112	Preset Color 28
						113-116	Preset Color 29
						117-120	Preset Color 30
						121-124	Preset Color 31
						125-128	Preset Color 32
						129-132	Preset Color 33
						133-136	Preset Color 34
						137-140	Preset Color 35
						141-144	Preset Color 36
						145-148	Preset Color 37
						149-152	Preset Color 38
						153-156	Preset Color 39
157-160	Preset Color 40						

ELATION | TVL CYC RGBW™ | dmx traits

ELATION® TVL CYC RGBW™
DMX Channel Values / Functions (14 DMX Channels)

Supports Software Versions: ≥ A: v1.2 | ≥ B: v1.1

Features subject to change without any prior written notice.

MODE / CHANNEL						VALUE	FUNCTION
4	6	7	8	10	14		
							COLOR MACROS - Continued
						161-164	Preset Color 41
						165-168	Preset Color 42
						169-172	Preset Color 43
						173-176	Preset Color 44
						177-180	Preset Color 45
						181-184	Preset Color 46
						185-188	Preset Color 47
						189-192	Preset Color 48
						193-196	Preset Color 49
						197-200	Preset Color 50
						201-204	Preset Color 51
				5	9	205-208	Preset Color 52
						209-212	Preset Color 53
						213-216	Preset Color 54
						217-220	Preset Color 55
						221-224	Preset Color 56
						225-228	Preset Color 57
						229-232	Preset Color 58
						233-236	Preset Color 59
						237-240	Preset Color 60
						241-244	Preset Color 61
						245-248	Preset Color 62
						249-252	Preset Color 63
						253-255	Preset Color 64
							SHUTTER / STROBE
						0-31	LEDs OFF
						32-63	LEDs ON
						64-95	Strobe Effect SLOW to FAST
		5	5	6	10	96-127	LEDs ON
						128-159	Pulse Effect SLOW to FAST
						160-191	LEDs ON
						192-223	Random Strobe SLOW to FAST
						224-255	LED ON
							MASTER DIMMER INTENSITY
	5	6	6	7	11	0-255	Intensity 0 to 100%
							MASTER DIMMER INTENSITY FINE
	6	7	7	8	12	0-255	Dimmer Intensity FINE Adjustment
							COLOR TEMPERATURE
			8	9	13	0	OFF
						1-255	0% = 7,200K - 100% = 3,200K
							DIMMER CURVES
						0-20	STANDARD
						21-40	STAGE
						41-60	TV
						61-80	ARCHITECTURAL
						81-100	THRATRE
				10	14	101-255	DEFAULT to UNIT CURVE SETTING

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu