

M-11 STAGE FOGGER

Antari continues to innovate with our first dual output designed M-11 fog machine. The M-11 features a dual output nozzle and dual pump system that can be controlled either independently or simultaneously, allowing for a wider range of volume adjustment and output flexibility. Automatic sequential pump operation can produce endless volumes of fog in continuous mode making the M-11 the highest output fog machine ever created from Antari. The versatile control options include built-in electronic timer, DMX with RDM, stand alone operation, and optional wireless remote. The M-11 is flexible enough to be used in small theaters and powerful enough to be used in the largest arenas.

Specification

- Input voltage	US model : AC 100-120V, 50/60Hz 13.3A EU model : AC 220-240V, 50/60Hz 6.67A	- DMX channels	1 or 3 channels
- Rated power	1600W	- Connection	Neutrik TRUE 1 Connector (Power) XLR 3-pin and 5-pin (DMX)
- Warm-up time	13 minutes (approx)	- Optional accessories	W-DMX-PCBR Wireless DMX WTR-20 Wireless WTR-70 Wireless DMX and Remote WTR-80 Wireless WTR-90 Wireless DMX
- Fluid consumption	400 ml/min (100% output)	- Dimension	L 675 W 320 H 285 mm (L 26.57 W 12.6 H 11.22 inch)
- Fluid tank capacity	10 Liters (2.64 gallon)	- Weight	25 kg (55.1 lbs)
- Compatible fluid	Antari FLG-10 Heavy Fog Fluid Antari FLR-10 Light Fog Fluid		
- Ambient temp/ range	0°C - 40°C (32°F - 104°F)		
- Control	Manual, Timer, DMX 512 Wireless (Optional) Wireless DMX (Optional)		



EFFECTS & FUNCTION



ACCESSORIES

OPTIONAL

W-DMX-PCBR W-DMX-PCB x 1 W-DMXR x 1	WTR-20 W-2 Transmitter x 1 W-2 Receiver x 1	WTR-70 W-2 Transmitter x 1 W-DMX-PCB x 1 W-DMXW2R x 1	WTR-80 W-2 Transmitter x 1 W-DMXW2R x 1	WTR-90 W-DMX-PCB x 1 W-DMXW2R x 1
---	---	--	---	---



FLUID

FLG-10 Heavy Fog Fluid
FLR-10 Light Fog Fluid



OPTIONAL