



PLATINUM SPOT LED PRO II™

SKU# **EPS060**

The new Platinum Spot LED PRO II™ features an extremely bright 170W Cool White LED engine, 15° to 33° motorized zoom, 7 dichroic colors plus white, 7 rotating, interchangeable, glass and 7 static metal gobos, frost filter hybrid wash effect, 3-facet rotating prism with 16 prism macros, motorized iris, focus, and dimming, high speed mechanical shutter and strobe, hibernation mode, 3 and 5pin DMX in/out connections, internal wireless DMX receiver, RDM (Remote Device Management), full color 180° reversible menu display with 6 button touch control panel, battery backup for display power, a multi-voltage universal auto switching power supply (100-240v), and flicker free operation for TV and FILM.

FEATURES

Extremely Bright Cool White LED Spot Illuminare

170W, 6,500K, >85CRI, 60,000 Hours

Low Heat, Quiet Operation, and Hibernation Mode

15° - 33° Motorized Zoom

7 Dichroic Colors + White

7 Rotating Interchangeable and 7 Static Gobos

3-Facet Rotating Prism and Frost Filter Hybrid Wash Effect

Internal EWDMX Wireless DMX Receiver

Flicker Free Operation For Broadcast TV and FILM



ELATION | PLATINUM SPOT LED PRO II™ | Product Specification Sheet

Specifications are subject to change without notice ©Elation Professional

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

PRODUCT SPECIFICATIONS

FEATURES

Extremely Bright Cool White LED Spot Illuminare
 Low Heat, Quiet Operation, and Hibernation Mode
 15° - 33° Motorized Zoom
 Frost Filter Hybrid Wash Effect
 Internal EWDMX Wireless DMX Receiver
 Flicker Free Operation For Broadcast TV and FILM

SOURCE

170W Cool White LED Engine
 60,000 Hour Average LED Life

PHOTOMETRIC DATA

6,500K, >85CRI
 12,200 LUX 1,113 FC @8.2' (2.5m) (15°Min Zoom Full ON)
 3,110 LUX 289 FC @8.2' (2.5m) (33° Max Full ON)

EFFECTS

Frost Filter Hybrid Wash Effect
 3-Facet Rotating Prism and Prism Macros
 Motorized Focus and Dimming 0% - 100%
 Iris: 5% - 100%
 Strobe: 1-18fps

COLOR

7 Dichroic Colors + White (Open)

GOBOS

7 Interchangeable / Rotating / Indexing Gobos
 Gobo Size: OD 1.06" (27mm) / ID 0.86" (22mm)
 7 Static / Indexing Gobos

CONTROL / CONNECTIONS

(3) DMX Channel Modes (17 / 15 / 22)
 RDM (Remote Device Management)
 6 Button Touch Control Panel
 Full Color 180° Reversible LCD Menu Display
 8 / 16 Bit Resolution Adjustable Movement
 Internal EWDMX Wireless DMX Receiver
 3pin & 5pin DMX In/Out

SIZE / WEIGHT

Length: 15.1" (384mm)
 Width: 14.8" (375mm)
 Vertical Height: 23.7" (601mm)
 Weight: 46.3 lbs. (21 kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
 290W Max Power Consumption
 -13°F to 113°F (-25°C to 45°C)

APPROVALS / RATINGS

CE Approved
 cETLus Approved
 RoHs Compliant
 IP20 Rated

INSTALLATION


Rigging: Clamps (Not Included)
 Working Position: Flat Surface / Inverted (180°)

INCLUDED ITEMS


Omega Brackets
 3pin DMX Cable



PHOTOMETRIC DATA




MIN ZOOM	m	ft	m	ft	m	ft
Distance	2.5	8.2	5	16.4	7.5	24.6
15° Beam Diameter	0.68	2.2	1.28	4.2	1.89	6.2
Full ON	lux	fc	lux	fc	lux	fc
	12,200	1133	3,488	324	1,637	152



MAX ZOOM	m	ft	m	ft	m	ft
Distance	2.5	8.2	5	16.4	7.5	24.6
33° Beam Diameter	1.44	4.7	2.88	9.4	4.33	14.2
Full ON	lux	fc	lux	fc	lux	fc
	3,110	289	781	73	360	33

DIMENSIONAL DIAGRAMS



OPTIONAL ACCESSORIES

ORDER CODE	ITEM
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
DRCPLAT	Dual Road Case For Platinum Spot LED PRO II™
DRCPLATQUAD	Quad Road Case For Platinum Spot LED PRO II™
ELO211	Eloader II™ Software Updater Box
EWDMXSYSTEM	Wireless DMX System (1 Transmitter, 1 Receiver)
EWDMXT	Wireless DMX Transmitter
EWDMXR	Wireless DMX Receiver
AC3PDMX5PRO	5 ft. (1.5m) 3pin PRO DMX Cable
AC3PDMX10PRO	10 ft. (3m) 3pin PRO DMX Cable
AC3PDMX15PRO	15 ft. (4.5m) 3pin PRO DMX Cable
AC5PDMX5PRO	5 ft. (1.5m) 5pin PRO DMX Cable
AC5PDMX10PRO	10 ft. (3m) 5pin PRO DMX Cable
AC5PDMX15PRO	15 ft. (4.5m) 5pin PRO DMX Cable
	Additional cable lengths available: 25, 50, 100 ft (7.5, 15.2, 30.5m)

Specifications are subject to change without notice ©Elation Professional

